



FIRE SLEEVE



1. Product Introduction

ZW TECH High Temperature Fire sleeve is made of braided e-grade glass fiber sleeve with silicone rubber coating, which designed as a kind of heavy duty jacket to protect different kinds of hoses, wires and cables from the hazards of high heat and occasional flame. Sheds molten metal splash in steel plants, glass plants, foundries, cutting and welding shops.

Good thermal insulation and fire proof performance make ZBAO TECH Fire sleeve reduce heat energy losses and protect employees from burning effectively.

2. Product Characters

Size/inner diameter	6mm-130mm
Colour	Typically in iron oxide red Other colours can be customized.
Working temperature	Continues working at 260 to 560°C Extreme temperature resistance with Max. duration of: 15-20 minutes +1000°C 15-30 seconds +1600°C
Rate voltage	7kv--25 kv
Character	High tempt. & flame resistant, insulation, anti-aging, avoiding splashing of the molten iron, abrasion resistant, water proof, oil proof, acid and alkali resistant.



3. Standard Specifications

ZW Part No.	Inner Dia.		Wall Thickness/mm	Roll Length/m
	mm	inch		
ZBAO06	6	1/4	1.5	20
ZBAO08	8	5/16	1.6	20
ZBAO10	10	3/8	1.8	20
ZBAO12/13	13	1/2	1.9	20
ZBAO15	15	5/8	2.1	20
ZBAO18	18	7/10	2.1	20
ZBAO20	20	3/4	2.4	20
ZBAO22	22	7/8	2.5	20
ZBAO25	25	1	2.6	20
ZBAO30	30	1 1/8	2.9	20
ZBAO32	32	1 1/4	3	20
ZBAO35	35	1 3/8	3.1	20
ZBAO38	38	1 1/2	3.2	20
ZBAO40	40	1 5/8	3.4	20
ZBAO45	45	1 3/4	3.4	20
ZBAO50	50	2	3.6	20
ZBAO55	55	2 1/4	3.7	20
ZBAO60	60	2 3/8	3.8	20
ZBAO65	65	2 1/2	3.8	20
ZBAO70	70	2 3/4	4	20
ZBAO75	75	3	4.1	20
ZBAO80	80	3 1/8	4.3	20
ZBAO85	85	3 1/4	4.3	20
ZBAO90	90	3 1/2	4.5	20
ZBAO95	95	3 3/4	4.5	20
ZBAO100	100	4	4.6	10
ZBAO110	110	4 3/8	4.7	10
ZBAO120	120	4 3/4	4.8	10
ZBAO130	130	5 1/8	5	10